

Description



The EDMO Lift'n'Lock is an Air Hydraulic Jack and Locking Support Stand combined in one unit. It complies with both the Australian Standard for Jacks and the Australian Standard for Vehicle Stands.

This version works using switches to air-activated hydraulic valves. This feature reduces the risk of operator error, and therefore risk of damage to the jack and locking systems. This version cannot be locked in the up-stroke. The axial valve fitted to the pump will prevent the pump from cycling when in neutral. Modifications to the body allow more ground clearance under the base for easier travel on rough terrain.

Specifications

Working Load Limit:	125,000kgs
Closed height:	727mm
Raised to first lock:	1158mm
Raised to last lock:	1560mm
	110PSI
Air supply required:	
Overall Dimensions:	
Length:	3450mm
Width:	590mm
Height:	1000mm
Weight:	600kg
Maximum operating height:	1560mm
<i>When raised and locked as a stand including a suitable 140mm diameter engagement extension.</i>	
Lead time:	12 weeks from receipt of deposit
Load Cap Supplied with Jack:	
Concave Load Cap	
Load Cap spigot hole is 51mm diameter	

ACCESSORIES

EDMOTivator

The 'EDMOTIVATOR' System powers a drive wheel using the jacks main pump and air supply. This gives the significant advantage of power and reliability over battery powered propulsion systems.

The 'EDMOTIVATOR' is operated from the handle of the jack. With the flick of a lever, the jack can be moved forward or back as required by the operator. The operator always retains full control of the motion. The speed is controlled by increasing or decreasing the air-supply via the attached ball valve. A jack with an 'EDMOTIVATOR' fitted can also be manoeuvred manually.

Air Line Remote Control

The air-line has the safety advantage of the operator being well clear of the load being jacked. The controls for the raising and lowering of the jack are connected by a 3 core flexible air line that allows the operator to move up to 5 meters away from the Jack and control the up and down functions.

Extensions

PART No:	DESCRIPTION:
LL12-41-100	100mm Extension
LL12-41-150	150mm Extension
LL12A-41-200	200mm Extension
LL12-41-250	250mm Extension
LL12A-41-300	300mm Extension

Extensions comply with the Australian Standard for jacks. However, be aware that when using the Lift'n'Lock as a stand the extensions will not comply with Australian Standard for stands.

Swivel Load Cap

The 360 degree rotation, 10 degree slope swivel load cap with a ribbed flat engagement for loads that will pivot as they are being raised.

The swivel of the load cap follows the movement of the load.

Capacity: 100,000 Kgs
Part no: LL12-001-076

Folding Handle

For further reach on the clearance height.
The handle can be pinned down.

Lead time: 12 weeks from receipt of deposit

Low Line Option - EDMO LL12AL

Your LL12A can be fitted with a Low Line Body and Handle to allow access to lift positions on lower clearance vehicles. No fork tine positions are built on this model.

Working Load Limit: 125,000 Kgs
Closed Height: 581 mm
Raised Last Lock Height: 866 mm

Load Cap Supplied with Jack:
Concave Load Cap

Lead time: 12 weeks from receipt of deposit

Additional Information

PLEASE ENQUIRE TO WORK WITH OUR ENGINEERS TO CREATE CUSTOM LOAD CAPS, EXTENSIONS, ENGAGEMENTS AND ACCESSORIES TO SUIT YOUR SPECIFIC REQUIREMENTS.

LOAD CAPS AND EXTENSIONS ARE TO BE USED UNDER AN ADVISORY STANDARDS CODE OF PRACTICE, IN CONJUNCTION WITH SITE SAFE OPERATING PROCEDURES/RISK ASSESSMENT.

Packed on half pallet for Australian market and on skid for exportation. For more packing options, long distance and export requirements, please enquire.